

F25



FLAT SUCTION CUP WITH CLEATS

- ▶ Suitable for flat objects.
- ▶ Good stability and little inherent movement.
- ▶ Recommended when the lifting force is parallel to the surface of the object.
- ▶ Cleats prevent thin, sensitive objects from being deformed and gives extra friction when the lifting force is parallel.

LIFTING FORCES & TECHNICAL DATA

Lifting force vertical to the surface, N, at vacuum level			Lifting force parallel to the surface, N, at vacuum level			Volume	Min. curve radius	Max. vertical movement	Weight rubber part
20 -kPa	60 -kPa	90 -kPa	20 -kPa	60 -kPa	90 -kPa	cm ³	mm	mm	g
9.0	19.5	25	8.0	9.0	10.0	1.1	22	1.5	1.8

MATERIAL SPECIFICATIONS


Material	Colour	Hardness °Shore A	Temperature range °C
Chloroprene, CR	Black	50	-40–110
Silicone, SIL	Red	50	-40–200

MATERIAL RESISTANCE


Material	Wear resistance	Oil	Weather & ozone	Hydrolysis	Petrol	Concentrated acids	Alcohol	Oxidation
Chloroprene, CR	Excellent	Fair	Good	Good	Fair	Poor	Good	Good
Silicone, SIL	Good	Poor	Excellent	Fair	Poor	Poor	Good	Excellent

ORDERING INFORMATION


Complete suction cups		Art. No.
A	Suction cup F25 Chloroprene, M5 female	0101292
B	Suction cup F25 Chloroprene, G1/8" male, with mesh filter	0101293
B	Suction cup F25 Chloroprene, G1/8" male, with mesh filter and dual flow control valve	0101299
C	Suction cup F25 Chloroprene, G1/8" male/M5 female, with mesh filter	0101297
C	Suction cup F25 Chloroprene, G1/8" male/M5 female, with dual flow control valve	0101301
D	Suction cup F25 Chloroprene, 5xM5 female	0101296
A	Suction cup F25 Silicone, M5 female	0101303
B	Suction cup F25 Silicone, G1/8" male, with mesh filter	0101304
C	Suction cup F25 Silicone, G1/8" male/M5 female, with mesh filter	0101308
C	Suction cup F25 Silicone, G1/8" male/M5 female, with dual flow control valve	0101312
D	Suction cup F25 Silicone, 5xM5 female	0101307
E	Suction cup F25 Chloroprene, G1/8" male/M5 female, PA	0109842
E	Suction cup F25 Silicone, G1/8" male/M5 female, PA	0110335




A




B



C




D



E

Rubber parts		Art. No.
Suction cup F25 Chloroprene		0101131
Suction cup F25 Silicone		0101132



Fittings		Art. No.
Fitting M5 female		3250003
Fitting M5 female, with dual flow control valve		3251001
Fitting G1/8" male, with mesh filter		3250085
Fitting G1/8" male, with mesh filter and dual flow control valve		3251002
Fitting G1/8" male/M5 female, with mesh filter		0101152
Fitting G1/8" male/M5 female, with dual flow control valve		3251004
Fitting 5xM5 female		0100260
Fitting 5xM5 female, with dual flow control valve		3251005
Fitting G1/8" male/M5 female, PA		3150196

For further information and dimensioned drawings, see SUCTION CUPS FITTINGS chapter.